

LoRaWAN autonomous indoor entry control sensor

SP Access Datasheet



Plug into the future!

Description

SP Access is a room access control sensor that signals the opening and closing of doors and operates on the basis of a magnetic effect. The sensor does not require an Internet connection and transmits notifications via the LoRaWAN radio network, for example, the Helium Network, and further to the SunPeak cloud service.

In case of illegal entry into the premises, you will receive an SMS notification or a push notification in the application. Together with other SunPeak sensors and actuators, you can easily create a monitoring and control system for your home or business, ensuring its safe and efficient operation.

Note: The device requires LoRaWAN Helium Network radio coverage, on the basis of which the SunPeak system operates. Before installation, do not forget to scan the QR code on the label of the device, then the data will be automatically received by your SunPeak application. For use with private LoRaWAN networks, you need to configure your network server using the included network keys.

Safety Information

Keep the device away from fire or hot environments.

Do not attempt to disassemble, repair, or modify the device. If you need service, please contact us

Do not use the device where wireless devices are not allowed.

CAUTION!

Avoid replacement of a battery with an incorrect type that can defeat a safeguard.

Avoid disposal of a battery into fire or a hot oven, or mechanically crushing or cutting a battery, as this can result in an explosion.


Do not leave a battery in an extremely high-temperature surrounding environment, as this can result in an explosion or the leakage of flammable liquid or gas.

Do not leave a battery subjected to extremely low air pressure, as this can result in an explosion or the leakage of flammable liquid or gas.



Quick start guide

- 1.Download the SunPeak app for Android or iOS or use the web version of the SunPeak <u>service.sunpeaki.com</u>
- 2. Log in using your phone number and add the device to your workspace by scanning the QR code on the device body or manually entering the serial number.
- 3. Install the two batteries from the supplied package observing the specified polarity in the main unit and close it with a click.



4. Install the main unit on the control doorway and magnetic unit on the door. Make sure that when closing the door, the units do not touch each other, while the distance between them does not exceed 5 mm.

Note: The direction of installation to each other is marked on the hulls of the units with a vertical line.

The device will not be able to connect to the Radio network automatically unless step 2 is completed.

5. Create your object in the SunPeak app or web version of the service, add this sensor to access control in the object settings.

Note: If the signal level at the installation site is sufficient, the system usually needs 15-30 minutes to receive and process data from the sensor, after which you will be able to see them in relation to the object.

The absence of data in the system, as well as regular flashes of red indicate insufficient LoRaWAN signal at the installation site. In this case, check the radio coverage in your location on our website and try to place the device, if possible, higher and in a more open space.



Specifications

Wireless Transmission	
Technology	LoRaWAN ®
Frequency	EU868/US915/IN865/AS923/AU915/RU864
Tx Power	+17dBm/+19dBm
Sensivity	-130 dBm
Mode	1.0.4 OTAA/ABP Class A
Operation	
Power On/Off	By batteries installing
Configuration	Not req., getting data via the SunPeak app
Physical Characteristics	
Power supply	3V (2x AAA size)
Battery life	>2 years (3 triggers per day)
Operating temperature	-40°C to +70°C
Ingress Protection	IP54
Dimension	70 x 30 mm
Installation	On the door and doorway with sticky tape

© SunPeak Innovations, All Rights Reserved. This document is for planning purposes only, and is not intended to modify or supplement any specifications or warranties relating to products of SunPeak Innovations. SunPeak Innovations may make changes to specifications and descriptions at any time, without notice.

